

# SHANDONG HUAJING GLASS CO.,LTD

Nanbeiyuan Rd, Naoshan Economic Development Zone, Qingzhou, Shandong, China Web:www.shhag.com

## The Classic Series

### Model : CD-01 & CD-02

2. Power supply: 115V/60Hz

5. Heated door frame

6. Self-closing function

8. Magnetic gasket

10. Argon gas filled

11. Reversible system

3. Two-pane glass: 4mm LOW-E electric heated

4. Door frame material: Aluminum alloy in silver

tempered glass + 4mm tempered glass

7. Middle slim handle (Mirror surface)

9. Stainless steel hinge system

The classic series is the standard one among all the door models.

2-pane glass with or without heater for cooler and 3-pane glass with heater for freezer.

Heated glass, door rail and frame rail to 100% guarantee NO condensation issue.

Reversible door system is available to make clients has option on the door opening direction.

We commit to supply customer the best satisfaction and easy installation on site!





	diass boot & Frame bescription
COOLER GLASS DOORS	FREEZER GLASS DOORS
Glass Door Parts :	Glass Door Parts :
1. Medium temperature	1. Low temperature

- 2. Power supply: 115V/60Hz
- 3. Three-pane glass: 4mm LOW-E electric heated tempered glass
- +3.2mm tempered glass + 4mm tempered glass
- 4. Door frame material: Aluminum alloy in silver
- 5. Heated door frame
- 6. Self-closing function
- 7. Middle slim handle (Mirror surface)
- 8. Magnetic gasket
- 9. Stainless steel hinge system
- 10. Argon gas filled
- 11. Reversible system
- 12. Temp sensor on each door to control heater working status
- 13. Glass door and frame wiring connection position (outlet 13. Glass door and frame wiring connection position (outlet position): one is in the middle position connection of the door position): one is in the middle position connection of the door body wiring, the other is in the top of the door shaft wiring Frame Parts:
  - 1. Frame material: Aluminum alloy in silver or black
  - 2. Frame with electric heater to avoid condensation
  - 3. Four-side flanged frame
  - 4. Strip waterproof LED
  - 5. Door stay open system
  - 6. Electric capacitor on the frame
  - 7. Frame with Temp sensor

SHELF & POST One door opening with one unit of shelf

- 1. Shelving size: 30"(W)X 27"(D)
- 2. Post height: 2000mm
- 3. Price tag length: 760mm
- 4. Material: Low carbon steel
- 5. Color: White or Black
- 6. Surface process: Powder coating to White (Wire rack, Post, Bracket and Stabilizer bar)
- 7. Using expansion screw to fix post on floor
- 8. Using bracket to connect front post with frame
- 8. Capacity per shelf: 80KG
- 9. Five to Seven shelves per door
- 10. With stabilizer bar between front and rear post

# Frame Parts:

- 1. Frame material: Aluminum alloy in silver
- 2. Frame with electric heater to avoid condensation

12. Temp sensor on each door to control heater working status

body wiring, the other is in the top of the door shaft wiring

- 3. Four-side flanged frame
- 4. Strip waterproof LED
- 5. Door stay open system
- 6. Electric capacitor on the frame

Net Opening Size For Classic Series Frame(Size can be customized)										
Door height: 67" - 73" - 75" Net Opening Heights for all door width's are 69 6/25" - 75 6/25" - 77 6/25"										
Doors	1	2	3	4	5	6	7	8	9	10
23"	25 1/21"	48 1/2"	72 1/14"	95 7/12"	119 1/11"	144 1/7"	167 2/3"	191 1/6"	214 2/3"	238 2/11"
26"	28 1/25"	54 5/9"	81 1/14"	107 7/12"	134 1/11"	162 1/7"	188 2/3"	215 1/6"	241 2/3"	268 2/11"
28"	30 1/25"	58 5/9"	87 1/14"	115 7/12"	144 1/11"	174 1/7"	202 2/3"	231 1/6"	259 2/3"	288 2/11"
30"	32 1/25"	62 5/9"	93 1/14"	123 7/12"	154 1/11"	186 1/7"	216 2/3"	247 1/6"	277 2/3"	308 2/11"
Doors	11	12	13	14	15	16	17	18	19	20
23"	263 3/13"	286 20/27"	310 1/4"	333 1/3"	357 2/7"	382 1/3"	405 21/25"	429 7/20"	452 43/50"	476 10/27"
26"	296 3/13"	322 20/27"	349 1/4"	268 1/3"	402 7/25"	430 1/3"	456 21/25"	483 7/20"	509 43/50"	536 10/27"
28"	318 3/13"	346 20/27"	375 1/4"	288 1/3"	432 2/7"	462 1/3"	490 21/25"	519 7/20"	547 43/50"	576 10/27"
30"	340 3/13"	370 20/27"	401 1/4"	308 1/3"	462 7/25"	494 1/3"	524 21/25"	555 7/20"	585 43/50"	616 10/27"















Hinge System Hold-open&Door Stop Magnetic Gasket Strip waterproof LED

Slim Handle/Full Length Handle

Temperature sensor

Energy	Consum <sub>l</sub>	ption da	ata sheet
um Temperature	Glass Door	& Frame	30" x 67"

Medium Temperature Glass Door & Frame 30" x 67"									
Item	Amperes				Watt				Note
Anti-sweat Heaters	2-Door	3-Door	4-Door	5-Door	2-Door	3-Door	4-Door	5-Door	
Doors	2.88	4.32	5.76	7.2	184	276	368	460	
Frames	1.1	1.44	1.85	2.13	126	165	213	245	
Vertical Lighting LED (120V)	0.79	1.1	1.37	1.66	72	108	144	180	
Low Temperature Glass Door & Frame 30" x 67"									
Item	Amperes				Watt				
The state of the s								III	

Low Temperature Glass Door & Frame SO X 67									
Item	Amperes					Watt			
Anti-sweat Heaters	2-Door	3-Door	4-Door	5-Door	2-Door	3-Door	4-Door	5-Door	
Doors	4.18	6.27	8.36	10.45	350	525	700	875	
Frames	2.45	3.48	4.11	5.48	281	401	472	630	
Vertical Lighting LED (120V)	0.79	1.1	1.37	1.66	72	108	144	180	

