

SHANDONG HUAJING GLASS CO.,LTD

Nanbeiyuan Rd, Naoshan Economic Development Zone, Qingzhou, Shandong, China Web:www.shhag.com

The Classic Series

Model: CD-01 & CD-02

The classic series is the standard one among all the door models.

2-pane glass with or without heater for cooler and 3-pane glass with heater for freezer.

Heated glass, door rail and frame rail to 100% guarantee NO condensation issue.

Reversible door system is available to make clients has option on the door opening direction.

We commit to supply customer the best satisfaction and easy installation on site!





Glass Door & Frame Description						
COOLER GLASS DOORS	FREEZER GLASS DOORS	SHELF & POST				
Glass Door Parts :	Glass Door Parts :	One door opening with one unit of shelf				
1. Medium temperature	1. Low temperature	1. Shelving size: 30"(W)X 27"(D)				
2. Power supply: 115V/60Hz	2. Power supply: 115V/60Hz	2. Post height: 2000mm				
3. Two-pane glass: 4mm LOW-E electric heated	3. Three-pane glass: 4mm LOW-E electric heated tempered glass	3. Price tag length: 760mm				
tempered glass + 4mm tempered glass	+3.2mm tempered glass + 4mm tempered glass	4. Material: Low carbon steel				
4. Door frame material: Aluminum alloy in silver	4. Door frame material: Aluminum alloy in silver	5. Color: White or Black				
5. Heated door frame	5. Heated door frame	6. Surface process: Powder coating to White				
6. Self-closing function	6. Self-closing function	(Wire rack, Post, Bracket and Stabilizer bar)				
7. Middle slim handle (Mirror surface)	7. Middle slim handle (Mirror surface)	7. Using expansion screw to fix post on floor				
8. Magnetic gasket	8. Magnetic gasket	8.Using bracket to connect front post with				
9. Stainless steel hinge system	9. Stainless steel hinge system	frame				
10. Argon gas filled	10. Argon gas filled	8. Capacity per shelf: 80KG				
11. Reversible system	11. Reversible system	9. Five to Seven shelves per door				
12.Temp sensor on each door to control heater working status	12.Temp sensor on each door to control heater working status	10. With stabilizer bar between front and				
13. Glass door and frame wiring connection position (outlet	13. Glass door and frame wiring connection position (outlet	rear post				
position): one is in the middle position connection of the door	position): one is in the middle position connection of the door					
body wiring, the other is in the top of the door shaft wiring	body wiring, the other is in the top of the door shaft wiring					
	Frame Parts :					
Frame Parts :	1. Frame material: Aluminum alloy in silver or black					
1. Frame material: Aluminum alloy in silver	2. Frame with electric heater to avoid condensation					
2. Frame with electric heater to avoid condensation	3. Four-side flanged frame					
3. Four-side flanged frame	4. Strip waterproof LED					
4. Strip waterproof LED	5. Door stay open system					
5. Door stay open system	6. Electric capacitor on the frame					

		Net	t Opening Size	e For Classi	c Series Fra	ame(Size c	an be customiz	ed)
	•	Door height	t: 67" - 73" - 75"	Net Opening	Heights for all	door width's a	re 69 6/25" - 75 6/25	" - 77
Doors	1	2	2	Л	-	6	7	

7. Frame with Temp sensor

Door height: 67" - 73" - 75" Net Opening Heights for all door width's are 69 6/25" - 75 6/25" - 77 6/25"										
Doors	1	2	3	4	5	6	7	8	9	10
23"	25 1/21"	48 1/2"	72 1/14"	95 7/12"	119 1/11"	144 1/7"	167 2/3"	191 1/6"	214 2/3"	238 2/11"
26"	28 1/25"	54 5/9"	81 1/14"	107 7/12"	134 1/11"	162 1/7"	188 2/3"	215 1/6"	241 2/3"	268 2/11"
28"	30 1/25"	58 5/9"	87 1/14"	115 7/12"	144 1/11"	174 1/7"	202 2/3"	231 1/6"	259 2/3"	288 2/11"
30"	32 1/25"	62 5/9"	93 1/14"	123 7/12"	154 1/11"	186 1/7"	216 2/3"	247 1/6"	277 2/3"	308 2/11"
Doors	11	12	13	14	15	16	17	18	19	20
23"	263 3/13"	286 20/27"	310 1/4"	333 1/3"	357 2/7"	382 1/3"	405 21/25"	429 7/20"	452 43/50"	476 10/27"
26"	296 3/13"	322 20/27"	349 1/4"	268 1/3"	402 7/25"	430 1/3"	456 21/25"	483 7/20"	509 43/50"	536 10/27"
28"	318 3/13"	346 20/27"	375 1/4"	288 1/3"	432 2/7"	462 1/3"	490 21/25"	519 7/20"	547 43/50"	576 10/27"
30"	340 3/13"	370 20/27"	401 1/4"	308 1/3"	462 7/25"	494 1/3"	524 21/25"	555 7/20"	585 43/50"	616 10/27"

Classic Series Standard Features



6. Electric capacitor on the frame













Hinge System Hold-open&Door Stop Magnetic Gasket

Strip waterproof LED **Energy Consumption data sheet**

Slim Handle/Full Length Handle

Temperature sensor

Medium Temperature Glass Door & Frame 30" x 75"									
Item	Amperes			Watt				Note	
Anti-sweat Heaters	2-Door	3-Door	4-Door	5-Door	2-Door	3-Door	4-Door	5-Door	
Doors	3	4.5	6	7.6	222	330	440	510	i
Frames	1.21	1.71	1.94	2.24	146	206	232	265	i
\(\(- \) \(\) \(\) \(\) \(\) \(\) \(\) \(0.70	1.1	4.27	1.00	72	100	4.4.4	100	1

